DATA PROJECTOR

D516

Great value high brightness ultra mobile projector

The Vivitek D516 SVGA digital projector offers 3000 ANSI Lumens of brightness, a 15000:1 contrast ratio. Thanks to the DLP® BrilliantColor™ technologies, the D516 delivers saturated colors and sharp, detailed images. The new high efficiency lamp that last up to 6000 hours makes the D516 an economic projector to run.

Features

- Native SVGA (800 x 600) resolution
- Super bright at 3000 ANSI Lumens for dazzling images
- 15000:1 contrast ratio for amazing picture quality
- High-efficiency lamp that last up to 6000 hours
- Connectivity options including: VGA-In, S-Video, Composite Video, and RS-232C
- 3D-Ready via DLP Link™
- Keypad lock prevents accidental system adjustments
- Ultra mobility thanks to light weight of 1.9kg

Photos

Specifications	
Brightness	3000 ANSI Lumens
Native Resolution	SVGA (800 x 600)
Maximum Resolution	UXGA (1600 x 1200)
Contrast Ratio	15000:1
Lamp Life and Type	4000/6000 Hours (std. / Boost. Mode), 190W
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio	1.92 - 2.14:1
Image Size (Diagonal)	40" - 300"
Projection Distance	1 - 10m
Projection Lens	F = 2.52 - 2.73, f = 24.34 - 25.95mm
Zoom Ratio	1.1x
Aspect Ratio	4:3 Native, 16:10, 16:9 Compatible
Offset	128%
Keystone Correction	±30° Vertical
Horizontal Frequency	15, 30 - 90kHz
Vertical Scan Rate	43 - 85Hz
Speakers	2 Watt
Lens Shift Range	N/A
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In, S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), RS-232
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x W)	261 x 190 x 78mm
Weight	1.9kg
Noise Level	30dB/33dB (Std./ Boost Mode)
Power Consumption	Supply: AC 100-240V, 50/60Hz Consumption: 230W (Std. Mode), 260W (Boost Mode), <1W(Standby)
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Remote, Carrying Case

© Copyright 2011 Vivitek Corporation. DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.
Address: Vivitek Corporation, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands, Tel: +31 20 655 0960, Fax: +31 20 655 0999, E-Mail: info@vivitek.eu